

BLUETTI Balcony Solar System

Scan the QR code to learn more





Contents

Chapter 1 1-5

What is BLUETTI Balcony Solar System?

Chapter 2 6-13

Why BLUETTI Balcony Solar System?

Chapter 3 14-15 Specifications

Chapter 4 16-17

Pre-order Options



What is BLUETTI Balcony Solar System?




BLUETTI
Balcony Solar System

The 1st Comprehensive Balcony Power Solution



BLUETTI Balcony Solar System is a highly efficient grid-tied energy storage system that consists of the solar panel, solar charge controller, microinverter, and battery. It stores extra solar energy generated during the daytime and provides power through the night, effectively reducing your peak-hour energy costs and cutting down your carbon footprint.





1


Solar panel captures the solar energy during the day. 2

Solar charge controller optimizes the conversion efficiency. 3

Microinverter converts the DC electricity into AC to power your devices.

4

Surplus energy stored in the battery for peak-hour use.





SAVE ON BILL



LOWER CARBON EMISSIONS




POWER THROUGH THE NIGHT

Affordable & Renewable Energy







^{*} The amount depends on regional guidelines and is subject to change anytime.
For further details, please inquire with your local authorities directly.

Energy Independence, Starts Here 05




Why BLUETTI Balcony Solar System?



Save up to 4.350 € for a 10 – year Use

Your Budget-Friendly Energy Solution

By storing the extra solar energy (up to 4,3 kWh) generated during the day and feeding back to your home for night-time use, you can save approximately 435 € per year on energy costs, meaning that your system can pay for itself in 5 years!



^{*} For reference ONLY. The actual savings may vary due to various factors, such as power consumption and local electricity price.

Energy Independence, Starts Here 07



Up to 98% High Efficiency Minimize Power Loss

The A80 microinverter converts the solar panel's direct current (DC) into alternating current (AC), which can be fed into the grid and ready to juice up household devices directly and efficiently, bringing extended runtime for your appliances.



Dual MPPT Solar Charge Controller



Higher Efficiency than Single Controller



Energy Loss

High Power Density Maximum Solar Harvest

Other Brands Solar Panel

176W/ m² 180

Surge Power Density


BLUETTI Solar Panel

180W/ m²

Surge Power Density

For reference ONLY.





IP65-rating Protection Durability and Safety Guaranteed







The balcony solar system is water and dust resistant to maintain excellent performance on your balcony. It also comes with the LiFePO4 battery for a prolonged lifespan and a 10-year warranty* to spare you a world of hassle.

^{*} The warranty for B210 battery is 5 years.



Quick Setup in Minutes





1-2 Person (s)

Space-saving





DIY Installation

Plug and Play

Smart Control with BLUETTI App



Fits Anywhere The Sun Shines

Balcony of Flat

Balcony of House

Backyard and Garden









Specifications













Flexible Panel Glass Panel

A80 Microinverter				
Rated Output	800W (800W-DE)	Maximum Input (PV)	1100W	
Rated Output Voltage	230V	MPPT Voltage Range	18-60V	
Weight	3.1kg/6.8lb	MPPT Efficiency	99%	
Connection Type	Bluetooth & WI-RI	Peak Efficiency	96.5%	
Ingress Protection	IP67	Dimensions	235×227×47mm (9.2×8.9×1.85in)	

D100S Solar Charge C	Controller			
PV Input Power	1000W	Operating Temperature	-40°C-85°C	
MPPT Efficiency	99%	Other Features	Voltage, Temperature Protection	
Output Efficiency	96%	Dimensions	235×225×47mm (9.2×8.8×1.8in)	
Noise Emission	<40dB	Weight	3kg/6.6b	
Ingress Protection	IP67			

B210 Bettery				
Capacity (1 B210 battery)	2,150Wh	Battery Scalability	4,300Wh with Two B210 Batteries	
Battery Type	L/FePO:	Weight	27.9kg/81.5lb	
Operating Temperature	-20°C-40°C	Noise Emission	<45dB	
Ingress Protection	IP85 Battery Life Cycles 3,000+ Cyclest		3,000+ Cycles to 80% Original Capacit	

Flexible Panel		Glass Panel	
Model No.	BFPV-255	Model No.	BGPV-410
PV Input Power	255W	PV Input Power	410W
Cell Type	PERCMONO	Cell Type	PERC MONO
Protection Rating	IP67	Ingress Protection	IP88
Wind Resistance Rating	37m/s (83 mph)	Wind Resistance Rating	37m/s(83 mph)
Dimensions	1410mm=1000mm=4mm	Dimensions	1722mm::1134mm::30mm
	(55.5 ln×39.4 ln×0.16 ln)		$(67.8 \text{ln}_{\times} 44.6 \text{ln}_{\times} 1.18 \text{ln})$
Connect Port	MC4	Connect Port	MC4
Weight	7kg/15.4lb	Weight	20.8kg/45lb
Open Circuit Voltage	51V	Open Circuit Voltage	37.4V
Voltage at Pmax	42.4V	Voltage at Pmax	31.42V
Shart Circuit Current	6.394	Short Circuit Current	13.84A

Pre-order Options



Choose Your Solutions

Pre-order Starting Oct. 2023





