

≡COFLOW

SOLAR PANEL

Contact Us:
ecoflow.com

NA/LA/APAC/MEA: support@ecoflow.com

EU: support.eu@ecoflow.com

AU: support.au@ecoflow.com

In The Box




Protective Case
and kickstand




Solar Panel




Snap Hook
x 4



User Manual
& Warranty Card




Solar Charging
Cable



MC4 Output Controller

How It Works




Solar Panel



Solar Charging Cable




XT60
INPUT PORT



EcoFlow DELTA
(Sold Separately)



EcoFlow RIVER
(Sold Separately)



Solar Panel



EcoFlow DELTA
(Sold Separately)




EcoFlow RIVER
(Sold Separately)




Your Solar Setup


1




2



3




4




This cable can only be used for connection between solar panels and energy storage. It is prohibited to be used for interconnection between solar panels or other connection purposes.

5



In order to increase the efficiency of the EcoFlow 160W Solar Panel, use it in direct sunlight, position it perpendicular to the sunlight, and make sure the solar panels are unobstructed.

6 Adjust the angle



For improved charging results, the Protective Case can also be used as a kickstand to prop up the solar panel at a 30°-80° angle.

Technical Specifications

160W Solar Panel
Rated Power: 160W(+/-5W)*
Open Circuit Voltage: 21.4V
Running Voltage: 18.2 V
Short Circuit Current: 9.6A
Running Current: 8.8A
Efficiency: 21%-22%
Cell Type: Monocrystalline silicon
Connector type: MC4
General
Solar Panel: Approx. 12.3 lbs(5.6KG)
Unfolded Dimensions: 26.9*62.6*1.0 in(68.5*159.0*2.5cm)
Folded Dimensions: 26.9*16.9*1.0 in(68.5*43.0*2.5cm)
Warranty: 12 months
Tested And Certified
     

60W Solar Panel
Rated Power: 60W(+/-5W)*
Open Circuit Voltage: 21.6V
Running Voltage: 18.2 V
Short Circuit Current: 3.5A
Running Current: 3.3A
Efficiency: 21%-22%
Cell Type: Monocrystalline silicon
Connector type: MC4
General
Solar Panel: 5.5 lbs(2.5KG)
Unfolded Dimensions: 21.1*32.4*1.0 in(53.5*82.2*2.5cm)
Folded Dimensions: 21.1*16.7*1.0 in(53.5*42.5*2.5cm)
Warranty: 12 months
Tested And Certified
     

*Standard Test Conditions:1000W/m2, AM1.5, 25°C

Temperature Coefficient Specifications

TKPower	-(0.39+/-0.02)%/k
TKVoltage	-(0.33+/-0.03)%/k
TKCurrent	+(0.06+/-0.015)%/k