

Certificate of Conformity

Certificate Number: 181016137GZU-001

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. This verification is part of the full test report<s> and should be read in conjunction with it ;

Applicant Name & Address:	SHENZHEN GROWATT NEW ENERGY TECHNOLOGY CO., LTD		
	1st East & 3rd Floor of Building A, Building B, Jiayu Industrial Park, #28,		
	GuangHui Road, LongTeng Community, Shiyan Street, Baoan District,		
	Shenzhen, P.R.China		
Product Description:	PV Grid inverter		
Ratings & Principle Characteristics:	See Annex to Test Certificate of Conformity		
Models:	MIN 2500TL-XH, MIN 3000TL-XH, MIN 3600TL-XH, MIN 4200TL-XH,		
	MIN 4600TL-XH, MIN 5000TL-XH, MIN 6000TL-XH		
Relevant Standards	EN 50438: 2013, Requirements for micro-generating plants to be connected In parallel with public low-voltage distribution networks Default settings type approval for Poland, Norway, Switzerland, Turkey and Hungary compliance, nevertheless, these also are applied for all the CENELEC members that do not have specific settings and requirements.		
Certificate Issuing Office:	Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China		
Date of Tests:	16 Oct 2018 to 21 Feb 2019		
Test Report Number(s):	181016137GZU-001		
Additional information in Appendix			

(muste

Signature

Name:Grady YePosition:ManagerDate:01 Mar 2019



This certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Certificate are relevant only to the sample tested/inspected. This Certificate by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program

Page 1 of 3



APPENDIX: Certificate of Conformity

This is an Annex to Certificate of Conformity with Verification/Report Number(s): 181016137GZU-001. The issuing office is Intertek Legal Entity as above.

Ratings and principal characteristics

Model	MIN 2500TL- XH	MIN 3000TL- XH	MIN 3600TL- XH	MIN 4200TL- XH		
Max.PV voltage	500	500 d.c.V		550 d.c.V		
PV voltage range	80-50	80-500 d.c.V		80-550 d.c.V		
PV lsc	16 d.c.A*2					
Max.input current	12.5 d.c.A*2					
Max. DC voltage		480 d.c.V				
DC voltage range		350-480 d.c.V				
Max. DC current		10 d.c.A				
Max.output power	2500W	3000W	3600W	4200W		
Max.apparent power	2500VA	3000VA	3600VA	4200VA		
Nominal output voltage	230 a.c.V					
Max.output current	11.3 a.c.A	13.6 a.c.A	16 a.c.A	19 a.c.A		
Nominal output Frequency	50Hz					
Power factor range	0.8Leading – 0.8 lagging					
Safety level		Class I				
Ingress Protection	IP 65					
Operation Ambient Temperature	-25℃ - +60℃					
Model	MIN 4600TL-XH MIN 500		DOTL-XH	MIN 6000TL-XH		
Max.PV voltage	550 d.c.V					
PV voltage range	80-550 d.c.V					
PV lsc	16 d.c.A*2					
Max.input current	12.5 d.c.A*2					
Max. DC voltage	480 d.c.V					
DC voltage range	350-480 d.c.V					
Max. DC current		10 d.c.A				

This certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Certificate are relevant only to the sample tested/inspected. This Certificate by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program



APPENDIX: Certificate of Conformity

This is an Annex to Certificate of Conformity with Verification/Report Number(s): 181016137GZU-001. The issuing office is Intertek Legal Entity as above.

Ratings and principal characteristics

Max.output power	4600W	5000W	6000W		
Max.apparent power	4600VA	4600VA 5000VA			
Nominal output voltage	230 a.c.V				
Max.output current	20.9 a.c.A	22.7 a.c.A	27.2 a.c.A		
Nominal output Frequency	50Hz				
Power factor range	0.8Leading – 0.8 lagging				
Safety level	Class I				
Ingress Protection	IP 65				
Operation Ambient Temperature	-25℃ - +60℃				
Software version	AL 1.0				

This certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Certificate are relevant only to the sample tested/inspected. This Certificate by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program