

## Certificate of Conformity

Certificate Number: CN-PV-220078

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

**Applicant:** Shenzhen Growatt New Energy Co., Ltd

4-13/F, Building A, Sino-German(Europe) Industrial Park, Hangcheng Ave,

Bao'an District, Shenzhen, China Static generator (PV Grid Inverter)

Product: Static generator (PV Grid Inverter)

See appendix of Certificate of Confe

Ratings & Principle See appendix of Certificate of Conformity Characteristics:

Model: MIN 2500TL-XE, MIN 3000TL-XE, MIN 3600TL-XE, MIN 4200TL-XE,

MIN 4600TL-XE, MIN 5000TL-XE, MIN 6000TL-XE, MIN 2500TL-X, MIN 3000TL-X, MIN 3600TL-X, MIN 4200TL-X, MIN 4600TL-X,

MIN 5000TL-X, MIN 6000TL-X

Brand Name<s>: GROWATT

**Product Complies with:** CEI 0-21:2019+V1:2020: Reference technical rules for the connection of

active and passive users to the LV electrical Utilities

Certificate Issuing Office Intertek Testing Services Ltd. Shanghai

Name & Address: West Area, 2nd Floor, No. 707, Zhangyang Road, China (Shanghai) Pilot Free

Trade Zone, Shanghai, P. R. China

Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012

**Test Report No.<s>:** 181016140GZU-001, Revision 2: 10 Mar 2022

Certification procedure: SMS-PV-OP-19
Product certification scheme type: Type test

/ susta

Additional information in Appendix.

**Signature** 

**Certification Manager: Grady Ye** 

Date: 06 May 2022

ACCREDIA 5

PRD N° 306B

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-220078.

Model	MIN 2500TL-XE MIN 2500TL-X	MIN 3000TL-XE MIN 3000TL-X	MIN 3600TL-XE MIN 3600TL-X	MIN 4200TL-XE MIN 4200TL-X	
Input (DC)					
Max. DC Voltage [V]	50	500		550	
PV Voltage Range [V]	80-	80-500		80-550	
Max. DC Input Current [A]	12.5*2				
Short Circuit Current Isc [A]	16*2				
Output (AC)					
Rated AC Power [W] (@230V,50Hz)	2500W	3000W	3600W	4200W	
Max. AC Apparent Power [VA]	2500VA	3000VA	3600VA	4200VA	
Max. AC Current [A]	11.3	13.6	16	19	
Nominal AC voltage	230				
Grid frequency	50Hz				
Power factor	0.8Leading ~ 0.8 Lagging				
Safety level	Class I				
Ingress Protection	IP 65				
Operation Ambient Temperature	-25℃ - 60℃				
Software version	AL1.0				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-220078.

Model	MIN 4600TL-XE MIN 4600TL-X	MIN 5000TL-XE MIN 5000TL-X	MIN 6000TL-XE MIN 6000TL-X		
Input (DC)					
Max. DC Voltage [V]		550			
PV Voltage Range [V]	80-550				
Max. DC Input Current [A]	12.5*2				
Short Circuit Current Isc [A]	16*2				
Output (AC)					
Rated AC Power [W] (@230V,50Hz)	4600W	5000W	6000W		
Max. AC Apparent Power [VA]	4600VA	5000VA	6000VA		
Max. AC Current [A]	20.9	22.7	27.2		
Nominal AC voltage	230				
Grid frequency	50Hz				
Power factor	0.8Leading ~ 0.8 Lagging				
Safety level	Class I				
Ingress Protection	IP 65				
Operation Ambient Temperature	-25℃ - 60℃				
Software version	AL1.0				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



Verification of certificate with test report: 181016140GZU-001, Revision 2: 10 Mar 2022

## TYPE OF APPARATUS:

( (Interface protection System (SPI) can be integrated to inverter with output power up to 11.08KW )

DISCONNECTION	INTERFACE PROTECTION	DEVICE FOR	ROTATING GENERATOR
DEVICE	DEVICE	CONVERSION	DEVICE
$\boxtimes$	$\boxtimes$	$\boxtimes$	

Manufacturer: Shenzhen Growatt New Energy Co., Ltd Apparatus type: Static generator (PV Grid inverter)

Model: MIN 2500TL-XE, MIN 3000TL-XE, MIN 3600TL-XE, MIN 4200TL-XE, MIN 4600TL-XE, MIN 5000TL-XE, MIN 6000TL-XE, MIN 2500TL-X, MIN 3000TL-X, MIN 3600TL-X,

MIN 4200TL-X, MIN 4600TL-X, MIN 5000TL-X, MIN 6000TL-X

Firmware Version: AL1.0

Number of phases: single-phase

Nominal power: See Certificate for each model

Remark: The devices are capable to limit I<sub>dc</sub> to 0.5% of the rated grid current

Having assessed the test report 181016140GZU-001, Revision 2: 10 Mar 2022 Issued by laboratory: Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Room 02, & 101/E201/E301/E401/E501/E601/E701/E801 of Room 01 18/F., No. 7-2. Caipin Road, Science

City, GETDD, Guangzhou, Guangdong, China

In compliant with ISO/IEC 17025:2017 Accreditation number: IAS TL-395

/ sustu

Having examined the ISO 9001 certificate of the manufacturer No: 02421Q32012223R0M issued by: UNIVERSAL CERTIFICATION CENTRE CO., LTD.

The indicated products above are complied with CEI 0-21:2019 + V1:2020: Reference technical rules for the connection of active and passive users to the LV electrical Utilities

Signature

Name: Grady Ye Date: 06 May 2022