



TAB e.module L5.1



Specifications

Basic Parameters	L5.1
Nominal Voltage (Vdc)	51.2
Nominal Capacity (Wh)	5120
Depth of Discharge (%)	97
Discharge Voltage (Vdc)	44.8
Charge Voltage (Vdc)	56.8
Charge/Discharge Current (A)	75 (recommended continuous)
	100 (maximum continuous)*
	200 (peak@15s)
Communication Port	CAN, RS485
Dimension (WxDxH, mm)	442x459x160
Weight (kg)	47.5
Working Temperature (°C)	0 ~ 45
Storage Temperature (°C)	-30 ~ 45 (up to 1 month)
	-20 ~ 35 (up to 6 months)**
Humidity (%)	20 ~ 95 (no condensation)
Altitude (m)	≤3000
IP Rating of Enclosure	IP20
Certificates	CE/IEC62619/IEC63056/IEC61000 ISO13849 - Performance level C

*The maximum continuous current for the battery is considered at a temperature of 10 ~ 35°C. Outside this temperature range, the current will be lower.

**The battery must be charged at least once every 6 months.

TAB tovarna akumulatorskih baterij d.d.

Polena 6, SI-2392 Mezica, Slovenia | Tel: +386 2 87 02 300 | Fax: +386 2 87 02 315 | Web: www.tab.si | E-mail: info@tab.si